



<b>MATERIAL</b>	LIMESTONE	<b>FORMAT</b>	TILE, SLAB
<b>ORIGIN</b>	TURKEY	<b>FINISH</b>	BRUSH/HONED/POLISHED/TUMBLED
<b>COLOR</b>	PALE GREEN, WHITE, LIGHT GREY	<b>UOM</b>	SF
<b>DIMENSION</b>	<b>PART NUMBERS</b>	<b>FINISH</b>	<b>SF/PIECE</b>
3 X 6 X 3/8	LIMSEAGRA0306T	TUMBLED	0.13 SF
4 X 4 X 3/8	LIMSEAGRA0404T	TUMBLED	0.11 SF
6 X 6 X 3/8	LIMSEAGRA0606T	TUMBLED	0.25 SF
12 X 12 X 3/8	LIMSEAGRA1212H	HONED	1.00 SF
12 X 24 X 1/2	LIMSEAGRA1224FL	FLAMED	2.00 SF
12 X 24 X 1/2	LIMSEAGRA1224H	HONED	2.00 SF
18 X 18 X 1/2	LIMSEAGRA1818H	HONED	2.25 SF
18 X 18 X 1/2	LIMSEAGRA1818P	POLISHED	2.25 SF
<b>APPLICATIONS</b>			
RESIDENTIAL, COMMERCIAL			
FLOORS/WALLS, INTERIOR/EXTERIOR, WET AREA (WHEN PROPERLY SEALED), (NO STEAM SHOWER), (NO POOLS)			

**Limestone Disclaimer:**

All Limestones should be cleaned and/or washed of any residue or dust on the surface of the stone prior to installation, grouting, and sealing. Allow 24-48 hours for drying prior to installation. Sealing limestone is highly recommended, please contact a professional for the most appropriate sealer for your application.

**WARNING: READ PRIOR TO INSTALLATION:**

Natural stones are products of nature and are prone to variations in color, texture, shading and veining that may differ from displays. Variations are not considered flaws as no two pieces of stone are alike. Prior to installation, ensure enough material, including waste is purchased for the entire project. Mix product from various cartons, and lay out all tiles and coordinating pieces to ensure optimal blending prior to installation. Natural stone products should be sealed prior to grouting. NO CLAIMS WILL BE ACCEPTED AFTER THE MATERIAL HAS BEEN INSTALLED