

specstones

Pearl **8"** **Character**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
	Ø medium of deep 8.59 mm
Impact Resistance	
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones

Pearl **8"** **Select**
Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones

Cotton
Name

8"
Width

Character
Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in) 5/8 16mm

Top Layer thickness (mm) 4 mm

Plywood thickness (mm) 12 mm

Length (ft) 6-8'

Width (in) 8"

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal $\pm 0.1\%$

Width Nominal $\pm 0.2\%$

Cupping 0.2% of nominal width

Banana 0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished

Bona® Ultra Matt Lacquer

Impact Resistance

Ø medium of deep 8.59 mm

Dimensional Stability (EN-1910):

Movement $\leq 0.29\%$

Formaldehyde Emission (EN-120)

E0. CARB2 Comply

Thermal conductivity (UNE-92-202)

0.14W/moK

Noise & Impact Isolation (UNE-EN-ISO 140-8)

ΔL_w : 17 dB

Fire Reaction (UNE 23727)

Cfl-S1

Profiling System

Tongue & Groove, beveled 2 sides

Warranty

www.rivaspain.com

Maintenance Instructions

www.rivaspain.com



specstones

Cotton
Name

8"
Width

Select
Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones

Mercury Name 8" Width Character Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	Δ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones

Mercury
Name

8"
Width

Select
Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	Δ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones

Smoke **8"** **Character**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones

Smoke **8"** **Select**
Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal \pm 0.1%
Width	Nominal \pm 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement \leq 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	Δ Lw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com



specstones



Sand **8"** **Character**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones



Sand **8"** **Select**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in) 5/8" (16mm)
 Top Layer thickness (mm) 4 mm (nominal)
 Plywood thickness (mm) 12 mm
 Length (ft) 6-8'
 Width (in) 8"

Finished Bona® Ultra Matt Lacquer
 Impact Resistance Ø medium of deep 8.59 mm
 Dimensional Stability (EN-1910): Movement ≤ 0.29%
 Formaldehyde Emission (EN-120) E0. CARB2 Comply
 Thermal conductivity (UNE-92-202) 0.14W/moK
 Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
 Fire Reaction (UNE 23727) Cfl-S1
 Profiling System Tongue & Groove, beveled 2 sides
 Warranty www.rivaspain.com
 Maintenance Instructions www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
 Width Nominal ± 0.2%
 Cupping 0.2% of nominal width
 Banana 0.1% nominal length



specstones



Earth **8"** **Character**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones



Earth **8"** **Select**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones



Crystal Name **8"** Character Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones



Crystal Name **8"** Width **Select** Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in) 5/8" (16mm)
 Top Layer thickness (mm) 4 mm (nominal)
 Plywood thickness (mm) 12 mm
 Length (ft) 6-8'
 Width (in) 8"

Finished Bona® Ultra Matt Lacquer
 Impact Resistance Ø medium of deep 8.59 mm
 Dimensional Stability (EN-1910): Movement ≤ 0.29%
 Formaldehyde Emission (EN-120) E0. CARB2 Comply
 Thermal conductivity (UNE-92-202) 0.14W/moK
 Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
 Fire Reaction (UNE 23727) Cfl-S1
 Profiling System Tongue & Groove, beveled 2 sides
 Warranty www.rivaspain.com
 Maintenance Instructions www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
 Width Nominal ± 0.2%
 Cupping 0.2% of nominal width
 Banana 0.1% nominal length



specstones

Krypton **8"** **Character**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones

Krypton **8"** **Select**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in) 5/8" (16mm)
 Top Layer thickness (mm) 4 mm (nominal)
 Plywood thickness (mm) 12 mm
 Length (ft) 6-8'
 Width (in) 8"

Finished Bona® Ultra Matt Lacquer
 Impact Resistance Ø medium of deep 8.59 mm
 Dimensional Stability (EN-1910): Movement ≤ 0.29%
 Formaldehyde Emission (EN-120) E0. CARB2 Comply
 Thermal conductivity (UNE-92-202) 0.14W/moK
 Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
 Fire Reaction (UNE 23727) Cfl-S1
 Profiling System Tongue & Groove, beveled 2 sides
 Warranty www.rivaspain.com
 Maintenance Instructions www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
 Width Nominal ± 0.2%
 Cupping 0.2% of nominal width
 Banana 0.1% nominal length



specstones



Amber **8"** **Character**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones



Amber **8"** **Select**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in) 5/8" (16mm)
 Top Layer thickness (mm) 4 mm (nominal)
 Plywood thickness (mm) 12 mm
 Length (ft) 6-8'
 Width (in) 8"

Finished Bona® Ultra Matt Lacquer
 Ø medium of deep 8.59 mm
 Dimensional Stability (EN-1910): Movement ≤ 0.29%
 Formaldehyde Emission (EN-120) E0. CARB2 Comply
 Thermal conductivity (UNE-92-202) 0.14W/moK
 Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
 Fire Reaction (UNE 23727) Cfl-S1
 Profiling System Tongue & Groove, beveled 2 sides
 Warranty www.rivaspain.com
 Maintenance Instructions www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
 Width Nominal ± 0.2%
 Cupping 0.2% of nominal width
 Banana 0.1% nominal length



specstones

Character
 Name **8"** **Character**
 Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones

Cigar **8"** **Select**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones

Gray Name **8"** Width Character Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in) 5/8" (16mm)
 Top Layer thickness (mm) 4 mm (nominal)
 Plywood thickness (mm) 12 mm
 Length (ft) 6-8'
 Width (in) 8"

Finished Bona® Ultra Matt Lacquer
 Impact Resistance Ø medium of deep 8.59 mm
 Movement ≤ 0.29%
 Formaldehyde Emission (EN-120) E0. CARB2 Comply
 Thermal conductivity (UNE-92-202) 0.14W/moK
 Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
 Fire Reaction (UNE 23727) Cfl-S1
 Profiling System Tongue & Groove, beveled 2 sides
 Warranty www.rivaspain.com
 Maintenance Instructions www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
 Width Nominal ± 0.2%
 Cupping 0.2% of nominal width
 Banana 0.1% nominal length



specstones

Gray **8"** **Select**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones



Black **8"** **Character**
 Name Width Grade

DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Character solid knots up to 3" (70mm) permitted. Open knots with fill less than 2" (50mm). Repaired cracks or splits within the planks are permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in) 5/8" (16mm)
 Top Layer thickness (mm) 4 mm (nominal)
 Plywood thickness (mm) 12 mm
 Length (ft) 6-8'
 Width (in) 8"

Finished Bona® Ultra Matt Lacquer
 Impact Resistance Ø medium of deep 8.59 mm
 Dimensional Stability (EN-1910): Movement ≤ 0.29%
 Formaldehyde Emission (EN-120) E0. CARB2 Comply
 Thermal conductivity (UNE-92-202) 0.14W/moK
 Noise & Impact Isolation (UNE-EN-ISO 140-8) ΔLw: 17 dB
 Fire Reaction (UNE 23727) Cfl-S1
 Profiling System Tongue & Groove, beveled 2 sides
 Warranty www.rivaspain.com
 Maintenance Instructions www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length Nominal ± 0.1%
 Width Nominal ± 0.2%
 Cupping 0.2% of nominal width
 Banana 0.1% nominal length



specstones

Black **8"** **Select**
 Name Width Grade



DESCRIPTION

This product has been manufactured according to the European Norm EN13489. Product: Multilayer Parquet Oak Plank.

COMPOSITION

Structure consists of a Birch Phenolic Plywood and an Oak Plank Top Layer, both elements glued with polyvinyl acetate adhesives, in accordance to the qualification CARB2.

GRADE

Select, solid knots up to 10 mm permitted in less 10% of the material. Open knots with fill, not permitted. Repaired cracks or splits within the planks are not permitted. No filled cracks/splits on the ends of the planks. Natural color variation is to be expected. Sapwood may be present and allowed if the color blends into the plank. No bleached sapwood allowed.

DIMENSIONS

Total thickness (in)	5/8" (16mm)
Top Layer thickness (mm)	4 mm (nominal)
Plywood thickness (mm)	12 mm
Length (ft)	6-8'
Width (in)	8"

Finished	Bona® Ultra Matt Lacquer
Impact Resistance	Ø medium of deep 8.59 mm
Dimensional Stability (EN-1910):	Movement ≤ 0.29%
Formaldehyde Emission (EN-120)	E0. CARB2 Comply
Thermal conductivity (UNE-92-202)	0.14W/moK
Noise & Impact Isolation (UNE-EN-ISO 140-8)	ΔLw: 17 dB
Fire Reaction (UNE 23727)	Cfl-S1
Profiling System	Tongue & Groove, beveled 2 sides
Warranty	www.rivaspain.com
Maintenance Instructions	www.rivaspain.com

DIMENSIONS TOLERANCES (EN 13647)

Length	Nominal ± 0.1%
Width	Nominal ± 0.2%
Cupping	0.2% of nominal width
Banana	0.1% nominal length



specstones

www.specstonesinc.com 415-684-1355 1500B Burke Ave. San Francisco